



Qty.	'A'	'B'	'C'	Options / Accessories	Tag

**STANDARD CONSTRUCTION**

- Fabricated of .063" thick aluminum alloy 3003-H14. All seams are fully welded and sprayed with protective coating.
- Mill finish is standard.
- If either dimension exceeds 90", multisection construction may be required.

**OPTIONS / ACCESSORIES**

**MATERIAL**

Aluminum products are available in either .081" or .125" thick 3003-H14 alloy.

**PLATFORM CAP**

A 3/4" plywood top with a metal cap fabricated of the same material as the product.

**WOOD NAILER**

Factory installed wood nailer for equipment mounting is mechanically fastened to top perimeter.

**GASKET**

1/4" thick polyurethane foam gasket can be installed, lining the entire top perimeter.

**INSULATION**

Available with 1" or 2" semi-rigid insulation.

**ACCESS PANELS**

To provide a passageway to internal equipment, an access opening is cut and lined with a protective vinyl edge seal and the cover panel is mechanically fastened over the opening. Minimum height restrictions apply.

**LOUVERED VENTS**

To provide an airflow through the curb, units are available with 6" wide x 7/8" high louvered vents, with 4 per side. Minimum height restrictions apply.

**FINISHES**

A wide selection of finishes including baked enamel, epoxy, Kynar, clear or color anodize, or prime coat.

PROJECT: \_\_\_\_\_  
 LOCATION: \_\_\_\_\_  
 ARCHITECT: \_\_\_\_\_  
 ENGINEER: \_\_\_\_\_  
 CONTRACTOR: \_\_\_\_\_  
 PO NUMBER: \_\_\_\_\_  
 DATE: \_\_\_\_\_