



Qty.	'A'	'B'	'C'	Options / Accessories	Tag

STANDARD CONSTRUCTION

- Fabricated of 18 gauge galvanized steel. All seams are fully welded and sprayed with protective coating.
- Mill finish is standard.
- If either dimension exceeds 90", multisection construction may be required.

PROJECT: _____
 LOCATION: _____
 ARCHITECT: _____
 ENGINEER: _____
 CONTRACTOR: _____
 PO NUMBER: _____
 DATE: _____

OPTIONS / ACCESSORIES

- MATERIAL**
Steel products are available in various gauges of galvanized, galvaneal, or stainless.
- PLATFORM CAP**
A 3/4" plywood top with a metal cap fabricated of the same material as the product.
- WOOD NAILER**
Factory installed wood nailer for equipment mounting is mechanically fastened to top perimeter.
- GASKET**
1/4" thick polyurethane foam gasket can be installed, lining the entire top perimeter.
- INSULATION**
Available with 1" or 2" semi-rigid insulation.
- ACCESS PANELS**
To provide a passageway to internal equipment, an access opening is cut and lined with a protective vinyl edge seal and the cover panel is mechanically fastened over the opening. Minimum height restrictions apply.
- LOUVERED VENTS**
To provide an airflow through the curb, units are available with 6" wide x 7/8" high louvered vents, with 4 per side. Minimum height restrictions apply.
- FINISHES**
A wide selection of finishes including baked enamel, epoxy, or prime coat.