

KN Series Submittal Data Sheet

JOB NAME:			
		ADDITIONAL INFORMATION:	
		Standard Features	Optional Equipment
		 Up to 99% Efficiency Full Modulation with 5:1 turndown Cast Iron Heat Exchanger Insulated Stainless Steel Jacket Tru-Flow™ Air Fuel Coupled System Flame Safeguard Control Flame Rod Rectification Direct Spark Ignition Communication Cable Low NOx Emissions Direct Vent T & P Gauge Reusable Air Filter Return / Supply Sensor (10K) 	☐ Propane Gas ☐ Outdoor Sensor w/Enclosure 10K ☐ Common Header Supply Sensor 10K ☐ 2 ½" Well ☐ 25' Length RS485 Communication Network Cable ☐ Protocarrier ☐ BACnet MSTP ProtoCessor* ☐ BACnet IP ProtoCessor* ☐ LonWorks ProtoCessor* ☐ N2 ProtoCessor* ☐ N2 ProtoCessor* ☐ Flow Switch ☐ LWCO * HeatNet bridge addressing worksheet required
		 Condensate Drain Self-Adjust for Altitude Air Vent Relief Valve (loose) Indoor Air Reset 	Gas Trains MA Code PA Code KY Code

- Communication Card which allows for:
 - o Boiler to Boiler Communications
 - o Firmware Updates
 - O Connections to Building Management Systems using Modbus Protocol
- HeatNet[™] Control
 - o Integrated Boiler Management System
 - o Communication Board
 - o Return Header Sensor
 - o Outlet Supply Sensor
 - o Modbus Protocol for Building Management System Communications