

**Model 5WK18/26
Air Conditioner/Heat Pump
Submittal Data**

SD-5WK18/26-1

STANDARD FEATURES

- Sleek Stainless Steel Cabinet
- Internally Insulated with Fiberglass Insulation
- Forward Curve Fan with Direct Drive Motor
- R410A Refrigerant
- 15 Amp Breaker
- Coaxial Copper Condenser Coil
- Touch Pad Electronic Control
- Condensate Pump
- 230V/1 Phase
- Heavy Duty Casters
- Off-Timer
- Thermostatic Control with Multi-Speed Fan
- Quick Connect Water Hose Kit
- Automatic Water Regulating Valve
- 4-Way Adjustable Air Discharge Grilles
- Rotary Compressor
- Washable Filters




SPECIFICATIONS

	5WK18	5WK26
CAPACITY DATA		
Cooling Capacity (Btu/hr) (a)	16,100	23,000
Heating Capacity (Btu/hr) (b)	19,100	27,300
ELECTRICAL DATA		
Volts (Single Phase)	230	230
Total Amps	6.6	10.0
Fuse/Breaker Amps (c)	15	15
CONDENSER WATER FLOW DATA		
GPM @ 86°F Entering Water Temperature	4.0	4.9
REFRIGERANT DATA CHARGE R410A (OUNCES)		
	22	39
DIMENSIONAL DATA (INCHES)		
Height with Casters	28.750	28.750
Height without Casters	26.375	26.375
Width	36.000	36.000
Depth	12.250	12.250
NET WEIGHT (LBS)		
	183	185
SHIPPING WEIGHT (LBS)		
	201	203

NOTES:

- (a) Cooling capacity rating test conditions : Evaporator Air 80°F D.B./67°F W.B. – Condenser Water - 85°F E.W.T./95°F L.W.T.
- (b) Reverse cycle units require 50°F minimum water inlet temperature during the heating cycle.
- (c) Time delay fuses and circuit breakers are recommended.

LDCI ELECTRICAL SERVICE PLUG CONFIGURATION

Model	Plug Configuration	Receptacle
5WK18/26 230V	 20 A 250V NEMA 6 - 20P	NEMA 6-20R



**260 North Elm St.
Westfield, MA 01085
Phone: 413-564-5520
Fax: 413-564-5815
www.Koldwave.com**

Project: _____ Date: _____
 Location: _____
 Customer: _____
 Engineer: _____
 Submitted By: _____
 For: Reference Approval Construction
 Unit Designation: _____
 Schedule Number: _____