

Model 6HK60/144
Air-Cooled Portable Air Conditioner
Submittal Data



SD-6HK60/144-2

STANDARD FEATURES

- All Steel, Painted Cabinets
- Internal Thermostat Settings
- Internally Insulated with Fiberglass Insulation
- R410a Refrigerant
- Fork Lift Slots and Lifting Lugs Standard
- Heavy Duty 4 Wheel Casters
- Cleanable Filters



SPECIFICATIONS

Model	6HK60BGA2ACA0	6HK144BBA2ACA0	6HK144BEA2ACA0
Cooling Capacity	60,000 Btu/h	144,400 Btu/h	144,400 Btu/h
Power Supply - V/P/Hz	230-1-60	230-3-60	460-3-60
Dimensions	29.5" W x 62.1" D x 58.1" H	34.3" W x 75" D x 71" H	34.3" W x 75" D x 71" H
Supply Duct Dia	Evap 16"		14" (2)
Connection	Condenser 20"		18" (2)
Return Duct Dia	Evap 16"		14" (2)
Connection	Condenser N/A		18" (2)
Weight	661 lbs.	1168.4 lbs.	1168.4 lbs.
Amp Draw	32 A	54 A	27 A
Air Filter Material		Vinyl Chloride	
Refrigerant		R-410a	
Operating Temp		64 - 113°F	
Condensate		Drain	
Typical Cooling Area	1830 sq. ft	3,767 - 4,951 sq. ft	



260 North Elm St.
 Westfield, MA 01085
Phone: 413-564-5520
Fax: 413-564-5815
 www.Koldwave.com

Project: _____ Date: _____
 Location: _____
 Customer: _____
 Engineer: _____
 Submitted By: _____
 For: Reference Approval Construction
 Unit Designation: _____
 Schedule Number: _____