

**Model 6SS24BGA2ACA0**  
**Split Portable Air Conditioner (60Hz)**  
**Submittal Data**

SD-6SS24-2

**STANDARD FEATURES**

- Compressor time delay
- Compressor overload protection
- High pressure switch
- Thermostat
- Anti-freeze Thermostat
- Self-diagnostic function
- Automatic restart
- Pre-Charged Glycol Lineset w/quick connect fittings
- Quick Connect communications between indoor and outdoor units

**SPECIFICATIONS**

Specification	Unit	6SS24BGA2ACA0
Cooling Capacity	BTU/H	22,000
Power Supply	Phase	Single Phase
	Volt	220
	Hz	60
Size (W x D x H)	In	27.75x13.78x36.54 (Indoor)
		27.56x10.83x27.56 (Outdoor)
Weight	lbs.	205 (Indoor) / 59.52 (Outdoor)
Current consumption	Amps	12.3
Power consumption	Kw	2.7
Air flow (Evaporator)	CFM (H/L)	565 / 653
Air filter (Condenser / Evaporator)		None / Vinylchloride
Refrigerant	Type	R-410A
Operating condition	°F	64.4 - 113
Supply and Return Water Lineset	Ft	25
Condensate tank	Liter	Drain Pump
Cooling area	Sq. Ft	645.84



**260 North Elm St.**  
 Westfield, MA 01085  
**Phone:** 413-564-5520  
**Fax:** 413-564-5815  
 www.Koldwave.com

Project: \_\_\_\_\_ Date: \_\_\_\_\_  
 Location: \_\_\_\_\_  
 Customer: \_\_\_\_\_  
 Engineer: \_\_\_\_\_  
 Submitted By: \_\_\_\_\_  
 For:  Reference  Approval  Construction  
 Unit Designation: \_\_\_\_\_  
 Schedule Number: \_\_\_\_\_