

Model 6SS24BGA2ACA0
Split Portable Air Conditioner (60Hz)
Submittal Data

SD-6SS24-3

STANDARD FEATURES

- Compressor time delay
- Compressor overload protection
- High pressure switch
- Thermostat
- Anti-freeze Thermostat
- Self-diagnostic function
- Automatic restart
- Pre-Charged Glycol Lineset w/quick connect fittings
- Quick Connect communications between indoor and outdoor units

SPECIFICATIONS

Specification	Unit	6SS24BGA2ACA0
Cooling Capacity	BTU/H	22,000
Power Supply	Phase	Single Phase
	Volt	208/230
	Hz	60
Size (W x D x H)	In	27.75x13.78x36.54 (Indoor)
		27.56x10.83x27.56 (Outdoor)
Weight	lbs.	205 (Indoor) / 59.52 (Outdoor)
Current consumption	Amps	12.3
Power consumption	Kw	2.7
Air flow (Evaporator)	CFM (H/L)	565 / 653
Air filter (Condenser / Evaporator)		None / Vinylchloride
Refrigerant	Type	R-410A
Operating condition	°F	64.4 - 113
Supply and Return Water Lineset	Ft	25
Condensate tank	Liter	Drain Pump
Cooling area	Sq. Ft	645.84



260 North Elm St.
 Westfield, MA 01085
Phone: 413-564-5520
Fax: 413-564-5815
 www.Koldwave.com

Project: _____ Date: _____
 Location: _____
 Customer: _____
 Engineer: _____
 Submitted By: _____
 For: Reference Approval Construction
 Unit Designation: _____
 Schedule Number: _____