

Model 8HK144

Air-Cooled Portable Air Conditioner

Submittal Data



SD-8HK144-2

STANDARD FEATURES

- In compliance with EPA requirements and worldwide trends, all Koldwave products are now made with low GWP refrigerants, identified by ASHRAE as class A2L. These models use R-454B refrigerant.
- All Steel, Painted Cabinets
- Internal Thermostat Settings
- Internally Insulated with Fiberglass Insulation
- Fork Lift Slots and Lifting Lugs Standard
- Heavy Duty 4 Wheel Casters
- Cleanable Filters



SPECIFICATIONS

Specification	Unit	8HK144BG	8HK144BH
Power Supply	Ph/V/Hz	3/230/60	3/460/60
Cooling Capacity	BTU/hr (kW/hr)	144,400 (42.32)	
Power Consumption	kW	20.7	16.46
Rated Current	A	54.3	26.4
Net Weight	lbs (kg)	1168 (530)	
Shipping Weight	lbs (kg)	1245 (565)	
Ambient Temperature Range	°F (°C)	64 - 113 (18 - 45)	
Dimensions W x D x H	in (mm)	35 x 75 x 71 (870 x 1904 x 1801)	
Indoor Air Flow	CFM (m³/hr)	4000 (6796)	
Refrigerant Type		R-454B	
Refrigerant Amount	oz (g)	264.6 (7500)	246.9 (7000)



260 North Elm St.
Westfield, MA 01085
Phone: 413-564-5520
www.Koldwave.com

09/26

Project: _____ Date: _____

Location: _____

Customer: _____

Engineer: _____

Submitted By: _____

For: Reference Approval Construction

Unit Designation: _____

Schedule Number: _____