

**Model 8HK60**  
**Air-Cooled Portable Air Conditioner**  
**Submittal Data**



SD-8HK60-1

**STANDARD FEATURES**

- In compliance with EPA requirements and world-wide trends, all Koldwave products are now made with low GWP refrigerants, identified by ASHRAE as class A2L. This model uses R32 refrigerant.
- All Steel, Painted Cabinets
- Internal Thermostat Settings
- Internally Insulated with Fiberglass Insulation
- Fork Lift Slots and Lifting Lugs Standard
- Heavy Duty 4 Wheel Casters
- Cleanable Filters



**SPECIFICATIONS**

	<b>Unit</b>	<b>8HK60</b>
Power Supply	Ph/V/Hz	1/220/60
Cooling Capacity	BTU/h (kW)	60,000 (17.58)
Power Consumption	kW	6.62
Rated Current	A	30.2
Net Weight	lbs (kg)	672 (305)
Gross Weight	lbs (kg)	773 (351)
Operating Ambient Temperature Range	°F (°C)	64 - 113 (18 - 45)
Dimensions WxDxH	in (mm)	30 x 59 x 58 (750 x 1482 x 1478)
Cool Air Flow	CFM (CMH)	1998 (3395)
Refrigerant Type		R32
Number of Compressors		2
Refrigerant Amount Per Compressor	oz (g)	33.5 (950)
Total Amount of Refrigerant	oz (g)	67 (1900)



260 North Elm St.  
 Westfield, MA 01085  
 Phone: 413-564-5520  
 Fax: 413-564-5815  
 www.Koldwave.com

4/2026

Project: \_\_\_\_\_ Date: \_\_\_\_\_  
 Location: \_\_\_\_\_  
 Customer: \_\_\_\_\_  
 Engineer: \_\_\_\_\_  
 Submitted By: \_\_\_\_\_  
 For:           Reference    Approval    Construction  
 Unit Designation: \_\_\_\_\_  
 Schedule Number: \_\_\_\_\_