6

Not to scale

STANDARD CONSTRUCTION

FRAME: .081" thk. (nominal) extruded aluminum, 6063-T52/T6 alloy.

BLADES: Stationary blades are .081" thk. (nominal) extruded

aluminum 6063-T52/T6 alloy. Adjustable blades are .125" thk. (nominal) extruded aluminum 6063-T52/T6 alloy.

Blades are approximately 41/2" on centers.

LOUVER FACE: Full width sill with head and blades contained

within jambs. Concealed mullion with continuous length

stationary blade.

LINKAGE: Extruded aluminum, concealed in the channel out of

the airstream. The pivots, which rotate in Celcon bearings, are .50" dia. Zinc plated machined steel. The pivot is locked to the 5/16" dia. aluminum linkage rod by a 1/4 - 20 set screw

with epoxy locking patch.

BEARINGS: Celcon bearing material so there will be no metal to metal

scraping.

SHAFTS: .50" dia. aluminum "Pin-Lock" rod.

SEALS: Extruded silicone rubber seals at blade edge. Foam on

bottom blade and polycarbonate jamb seals. Standard stainless steel at jambs required on painted louvers.

SCREEN: (When indicated, in a removable frame)

½" flattened aluminum, .051" thk.,

-or-Insect screen 18/16 aluminum mesh, .011" dia., ½" sq. mesh intermediate double crimped -or-

aluminum wire, .063" dia.

FINISH: Mill.

OPTIONS

Finishes - Enamels, Epoxies, etc.


Other screens available.


Actuators - Electric, Pneumatic, Manual, etc.

- 1. ½" nominal deduction will be made to the opening size given.
- 2. Approximate shipping weight is 5.0 lbs./sq.ft.

LOUVER SIZES

| Min Panel | Max Single Panel | | | | |
|-------------|------------------|--|--|--|--|
| 12"W x 16"H | 96"W x 72"H | | | | |





Louver Height

(in.)

41/2

* Visible Mullion required every 96" maximum.

| Item # | Otre | Width | Height | Width | Height | Mullion | Type | Location | | | VONAL PO |
|----------------|------|--------|---------|-------|--------|---------|---------|----------|---|----------|-----------|
| | Qty | Openii | ng Size | Louve | r Size | Mullion | Screens | | | <u>U</u> | nion Made |
| Arch. / Eng. : | | | | | | EDR: | | ECN: | J | lob: | |
| Contractor: | | | _ | | | | | _ | - | | |
| | | | | | | | | | | | |

In the interest of product development, Louvers & Dampers reserves the right to make changes without notice.

