
DOMINATOR 400

Category I or Category III Appliance

(see Installation and Operation Manual for venting information)



Boilers & Water Heaters not available for sale in Canada due to NRCan regulations.

LEFT VIEW

RSUB-28-E

Notes:

Dimensions are approximate and should not be used to "rough-in" equipment.

FRONT VIEW

- Dimensions are subject to change without notice.
 All dimensions are in inches (cm).
 Symbol indicates center of gravity.

BOILER CERTIFIED RATINGS & CAPACITIES

Fuel Type	Natural/Propane Gas	Boiler FLA	3.8*
Input BTU/hr.	399,000 / 117 kW	Min. Gas Pressure Required	7" WC**
Output BTU/hr.	335,160 / 98 kW	Max. Gas Pressure Allowed	14" WC
Electrical Requirements	120VAC/ 1 ph/ 60 hz	Operating Weight	490 lbs. / 222 kg.

BOILER / WATER HEATER TRIM & CONTROLS

Main Gas Valve	Honeywell VR8305 3/4"	Pilot Valve	Honeywell VR8205	
Firing Valve	Honeywell B200T1025 3/4"	Air Switch	Cleveland RSS-495	
Ignition Control	UTC 1003-61A	Blower Motor	1/5 hp - FLA 3.0	
Operating Control	Tekmar BTC-2PA	Relief Valve - DB	3/4" x 3/4" set @ 50 psi	
High Limit	Honeywell L4008E	Flow Switch	TACO	

A.S.M.E.

ASME Sect IV Htg Surface	50.0 Sq. Ft. / 4.65 Sq. M.	Design Data	Max. 160 psig & 250°F
Water Volume 3.6 gal / 13.6 Liters			

^{*} Add circulator amps.

BOILER TEMPERATURE RISE / PRESSURE DROP

15°F / 8.3°C		20°F / 11.1°C			25°F / 13.9°C						
Flow	Rate	Pressur	e Drop	Flow	Rate	Pressur	e Drop	Flow	Rate	Pressur	e Drop
GPM	L/s	Ft	kPa	GPM	L/s	Ft	kPa	GPM	L/s	Ft	kPa
44.7	2.8	0.48	1.4	33.5	2.1	0.28	0.8	26.8	1.7	0.19	0.5

Boilers & Water Heaters not available for sale in Canada due to NRCan regulations.

REP FIRM	
SUBMITTED BY	
JOB NAME	
ARCHITECT	
ENGINEER	
CONTRACTOR	
DATE	

DOMINATOR 400

Category I or Category III Appliance

(see Installation and Operation Manual for venting information)



A Division of Mestek, Inc. Westfield, MA 01085 (833) 265-5371

^{**} For incoming gas pressures lower than 7"WC natural or 11"WC propane, consult factory.