



Dominator Series Submittal Data

JOB NAME: _____

LOCATION: _____

ARCH/ENGR: _____

CONTRACTOR: _____

MODEL NO: _____

TYPE GAS: _____

BTU INPUT/OUTPUT: _____

ADDITIONAL INFORMATION:

Standard Features

- Up to 85% Efficiency
- Glass Lined Headers
- National Board Certified
- Integral PID Staging Control
- Outdoor Reset
- Low NO_x
- Slide Out Heat Exchanger
- Finned Copper Tube Heat Exchanger
- Tekmar Sensor
- Low Voltage Controls
- ASME Pressure Relief Valve Mounted
- Pump Delay Control
- LED Diagnostic Panel
- Uginox Alloy Stainless Steel Burners
- 2 Stage Firing (400 – 2100) (300 On/Off ONLY)
- 4 Stage Firing (1050 – 2100)
- Sealed Combustion Chamber
- Temperature/Pressure Gauge (Boiler)
- Flow Switch Mounted and Wired
- FM Compliant Gas Train
- Category I or III Venting
- Leak Test Valves
- Side Combustion Air Intake (300 – 2100)
- Rear Combustion Air Intake (750 – 2100)
- Direct Vent up to 35' Equivalent
- SCAQMD Rule 1146.2
- Ventura County APCD Rule 74.11.1
- CSA Designed Certified and Listed

Optional Equipment

Bronze Headers
Propane Gas
Cupronickel Heat Exchanger
Wired & Mounted Flange
5' Pump Pigtail
Alarm Bell
Flame Failure Dry Contact
Main Flame Status Contact
Enable/Disable Relay 24V
Enable/Disable Relay 120V
Low Gas Pressure Switch
High Gas Pressure Switch
Right Hand Water Connection
C.A.D. Dry Contact
Freeze Protection Kit
Stainless Steel Jacket
Power Venting Wiring
3PH Pump Contactor (shipped loose)
Remote/Local Switch
Sidewall Vent Kit
Sidewall Vent Kit w/Air Intake Hood
Vent Termination Hood
Air Intake Hood
Barometric Damper
Outdoor Installation
Pump
Rack Kit

Gas Trains

☐ CSD-1 Code