RBI

Torus Series Submittal Data Sheet (Models 300 – 1000)

JOB NAME: _____

LOCATION: _____

ARCH/ENGR: _____

CONTRACTOR: _____

MODEL NO: _____

TYPE GAS: _____

BTU INPUT/OUTPUT: _____

ADDITIONAL INFORMATION:

Standard Features

- Up to 97% Boiler Efficiency
- Up to 98% Water Heater Efficiency
- Full Modulation with 10:1 turndown
- Stainless Steel Water Tube Heat Exchanger
- Painted Carbon Steel Jacket
- 7" Diagonal Touch Screen Display
- Tru-Flow™ Air Fuel Coupled System
- Manual Reset LWCO
- Flow Switch Mounted
- Relief Valve
- Flame Module Control
- Flame Rod Rectification
- Low Air Pressure Switch
- Condensate Drain
- Temperature/Pressure Gauge
- PVC (US Only) / CPVC
- 120V 1HP Power Supply
- Blocked Flue Switch
- Remote Local Switch
- Manual Reset High Limit
- Variable Speed Blower
- Air Vent
- Versatile Footprint Fits Through 36' Door (All Sizes)

Optional Equipment

- ☐ Propane
- ☐ Dual Fuel
- ☐ Common Header Supply Sensor 10K
- ☐ 3" Well
- ☐ Digital Flow Sensor
- ☐ Main Flame Status Contact
- ☐ Freeze Protection Kit
- ☐ Valve Proving System (650 – 1000)
- ☐ High Gas Pressure Switch – CSD-1 (Manual Reset)
- ☐ Low Gas Pressure Switch – CSD-1 (Manual Reset)
- ☐ Motorized Valve / Wiring 120V ☐ Pwr Opn/Sprg Clsd
         ☐ Sprg Opn/Pwr Clsd   ☐ Pwr Opn/Pwr Clsd
- ☐ Flue Outlet Damper / Wiring _____V ☐ On/Off ☐ Mod
- ☐ Vent Termination Hood
- ☐ Air Intake Hood
- ☐ Pump (Shipped Loose)
- ☐ Stainless Steel Vent
- ☐ Polypropylene Vent
- ☐ Concentric Vent (300 – 500)
- ☐ BACnet ProtoCessor (MSTP)*
- ☐ BACnet ProtoCessor (IP)*
- ☐ LonWorks ProtoCessor*
- ☐ N2 ProtoCessor*

HeatNet bridge addressing worksheet required

Gas Trains

- ☐ CSD-1
- ☐ IRI (Valve Proving System & CSD-1)
- ☐ FM
- ☐ KY Code

- HeatNet™ Control
    - Full Linear Modulation Control
    - Integrated Boiler Management System
    - Diagnostic Annunciator Touch Screen
    - 4-20 mA External Modulation Contact
    - Inlet/Outlet Temperature Sensors
    - Modbus Standard Protocol