

| JOB NAME:   |  |
|---|--|
| LOCATION:   |  |
| ARCH/ENGR:  |  |
| CONTRACTOR:   |  |
| MODEL NO:   |  |
| TYPE GAS:   |  |
| BTU INPUT/OUTPUT:   |  |
| ADDITIONAL INFORMATION:   |  |
| Standard Features   | Optional Equipment   |
| • Up to 97.5% Boiler Efficiency   | □ 208V 1PH (WB/WW2000)   |
| • Up to 98.0% Water Heater Efficiency   | □ 208/230V 3PH (WB/WW2000)V  |
| • Full Modulation with up to 10:1 turndown  | □ 208V 3PH (WB/WW2500-4000)  |
| • Stainless Steel Water Tube Heat Exchanger   | □ 460/600V 3PH (WB/WW2000-4000)V   |
| <ul> <li>Painted Carbon Steel Jacket</li> </ul>                                       | ☐ Common Header Supply Sensor 10K  |
| • 7" Diagonal Touch Screen Display  | □ 3" Well  |
| • Tru-Flow™ Air Fuel Coupled System   | ☐ Outdoor Sensor w/Enclosure 10K   |
| Flame Module Control  | ☐ High Gas Pressure Switch (Manual Reset)  |
| Flame Rod Rectification   | ☐ Low Gas Pressure Switch (Manual Reset)   |
| Low Air Pressure Switch   | ☐ Main Flame Status Contact  |
| • Leak Test Valves  | ☐ Valve Proving Switch   |
| • Condensate Drain  | ☐ Freeze Protection Kit  |
| • Temperature/Pressure Gauge  | ☐ Motorized Valve/Wiring 120V ☐ Pwr Opn/Sprg Clsd  |
| • Low Gas Pressure Switch (2500-4000)   | □ Sprg Opn/Pwr Clsd □ Pwr Opn/Pwr Clsd   |
| <ul> <li>High Gas Pressure Switch (2500-4000)</li> <li>Remote Local Switch</li> </ul> | <ul> <li>□ Flue Outlet Damper/WiringV □On/Off □Mod</li> <li>□ Vent Termination Hood</li> </ul> |
| <ul> <li>Remote Local Switch</li> <li>Manual Reset High Limit</li> </ul>              | ☐ Air Intake Hood  |
| Variable Speed Blower   | ☐ Pump (Shipped Loose)   |
| • Flow Sensor Mounted   | □ PVC Vent Kit   |
| • Air Vent  | □ PP Vent Kit  |
| Relief Valve  | □ BACnet ProtoCessor (MSTP)*   |
| Manual Reset LWCO   | □ BACnet ProtoCessor (IP)*   |
| Blocked Flue Switch   | ☐ LonWorks ProtoCessor*  |
| • CSD-1 Compliant Train   | □ N2 ProtoCessor*  |
| <ul> <li>Versatile Footprint Fits Through 36" Door<br/>(All Sizes)</li> </ul>         | *HeatNet bridge addressing worksheet required.   |
|   | Gas Trains   |
|   | □ CSD-1  |
|   |  |
|   | ☐ FM   |
|   | □ KY Code  |

- HeatNet<sup>™</sup> Control
  - o Full Linear Modulation Control
  - o Integrated Boiler Management System
  - o Diagnostic Annunciator Touch Screen
  - o 4-20 mA External Modulation Contact
  - o Inlet/Outlet Temperature Sensors
  - o Modbus Standard Protocol