



ADDITIONAL INFORMATION:

- Up to 97.5% Boiler Efficiency
- Up to 98.0% Water Heater Efficiency
- Full Modulation with 10:1 turndown
- Stainless Steel Water Tube Heat Exchanger
- Painted Carbon Steel Jacket
- Relief Valve
- 7" Diagonal Touch Screen Display
- Tru-Flow™ Air Fuel Coupled System
- Flame Module Control
- Flame Rod Rectification
- Low Air Pressure Switch
- Manual Reset LWCO
- Condensate Drain
- Temperature/Pressure Gauge
- Low Gas Pressure Switch (2500-4000)
- High Gas Pressure Switch (2500-4000)
- Remote Local Switch
- Manual Reset High Limit
- Variable Speed Blower
- Flow Switch Mounted
- Air Vent
- Blocked Flue Switch
- Versatile Footprint Fits Through 36" Door (All Sizes)

Dual Fuel _____ Propane _____
 208/230V 1PH _____ 3PH _____ (WB/WW2000) _____ V
 208V 3PH (WB/WW2500-4000)
 460/600V 3PH (WB/WW2000-4000) _____ V
 Common Header Supply Sensor 10K
 3" Well
 Digital Flow Sensor
 Outdoor Sensor w/Enclosure 10K
 High Gas Pressure Switch (Manual Reset) (1250-2000)
 Low Gas Pressure Switch (Manual Reset) (1250-2000)
 Main Flame Status Contact
 Valve Proving Switch
 Freeze Protection Kit
 Motorized Valve Wiring 120V Pwr Opn/Sprg Clsd
 Sprg Opn/Pwr Clsd Pwr Opn/Pwr Clsd
 Flue Outlet Damper/Wiring _____ V On/Off Mod
 Vent Termination Hood
 Air Intake Hood
 Pump (Shipped Loose)
 PVC Vent Kit
 PP Vent Kit
 BACnet ProtoCessor (MSTP)*
 BACnet ProtoCessor (IP)*
 LonWorks ProtoCessor*
 N2 ProtoCessor*

**HeatNet bridge addressing worksheet required.*

CSD-1
IRI (Valve Proving System & CSD-1)
FM
KY Code

- HeatNet™ Control
 - Full Linear Modulation Control
 - Integrated Boiler Management System
 - Diagnostic Annunciator Touch Screen
 - 4-20 mA External Modulation Contact
 - Inlet/Outlet Temperature Sensors
 - Modbus Standard Protocol