



LCD Series Submittal Data

JOB NAME: _____

LOCATION: _____

ARCH/ENGR: _____

CONTRACTOR: _____

MODEL NO: _____

TYPE GAS: _____

BTU INPUT/OUTPUT: _____

ADDITIONAL INFORMATION:

Standard Features

- 82% Efficiency
- Glass Lined Headers
- National Board Certified
- Integral PID Staging Control
- Low NO_x
- Slide Out Heat Exchanger
- Finned Copper Tube Heat Exchanger
- ASME Pressure Relief Valve Mounted
- Pump Delay Relay
- Indicator Light Panel
- Uginox Alloy Stainless Steel Burners
- On/Off Firing
- 2 Stage Firing (600 – 1970)
- Sealed Combustion Chamber
- Temperature/Pressure Gauge
- Thermometer
- Flow Switch Mounted and Wired
- Low Voltage Controls
- FM Compliant Gas Train
- Category I or III Venting
- 20 Amp Pump Contactor Single Phase
- Leak Test Valves
- Side Combustion Air Intake (225 – 1970)
- Rear Combustion Air Intake (750 – 1970)
- Direct Vent up to 35' Equivalent
- SCAQMD Rule 1146.2
- Ventura County APCD Rule 74.11.1
- CSA Designed Certified and Listed

Optional Equipment

- Bronze Headers
- Propane Gas
- Cupronickel Heat Exchanger
- Wired & Mounted Flange
- 5' Pump Pigtail
- Alarm Bell
- Flame Failure Dry Contact
- Enable/Disable Relay 24V
- Low Gas Pressure Switch
- High Gas Pressure Switch
- Right Hand Water Connection
- C.A.D. Dry Contact
- Freeze Protection Kit
- Stainless Steel Jacket
- Power Venter Wiring
- Outdoor Reset/Domestic Override (400 - 1970)
- Sidewall Vent Kit
- Sidewall Vent Kit w/Air Intake Hood
- Vent Termination Hood
- Air Intake Hood
- Barometric Damper
- Outdoor Installation
- Pump
- Rack Kit

Gas Trains

- CSD-1 Code