



**STYLE Light Commercial "LCS-10"**

**COPPER/ALUMINUM ELEMENT RATINGS**  
 ALL RATINGS ARE BASED ON 3 FPS VELOCITY, 65° EAT

TUBE SIZE	CATALOG DESIGNATION	FIN SIZE HEIGHT X WIDTH	FINS PER FT.	FIN THICKNESS IN INCHES	TIERS AND CENTERS IN INCHES	MTG. HEIGHT IN INCHES	STEAM 215°F FACTOR	HOT WATER (AVG.)									
								200°	190°	180°	170°	160°	150°	140°	130°	120°	
								CORRECTION FACTORS FOR AVERAGE WATER TEMPERATURES									
								1.00	0.86	0.78	0.69	0.61	0.53	0.45	.40	.33	.26
3/4"	R02	2-1/2" x 2-3/4"	60	.010	1	14-1/4	1140	980	890	790	700	600	510	460	380	300	
					2 - 3-1/2 CL	14-1/4	1560	1340	1220	1080	950	830	700	620	510	410	
1"	R03	2-1/2" x 2-3/4"	55	.011	1	14-1/4	1090	940	850	750	660	580	490	440	360	280	
					2 - 3-1/2 CL	14-1/4	1600	1380	1250	1100	980	850	720	640	530	420	
3/4"	R04	3-3/4" x 2-3/4"	50	.014	1	14-1/4	1170	1010	910	810	710	620	530	470	390	300	
1"	R05	3-3/4" x 2-3/4"	50	.011	1	14-1/4	1130	970	880	780	690	600	510	450	370	290	
1-1/4"	R08	3-3/4" x 2-3/4"	50	.020	1	14-1/4	1150	990	900	790	700	610	520	460	380	300	
1"	R06	5" x 2-3/4"	40	.020	1	14-1/4	1200	1030	940	830	730	640	540	480	400	310	
1"	R07	5" x 2-3/4"	50	.020	1	14-1/4	1210	1040	940	830	740	640	540	480	400	310	
1-1/4"	R09	5" x 2-3/4"	40	.020	1	14-1/4	1150	990	900	790	700	610	520	460	380	300	
1-1/4"	R10	5" x 2-3/4"	50	.020	1	14-1/4	1230	1060	960	850	750	650	550	490	410	320	

**STYLE Light Commercial "LCS-10"**

**STEEL ELEMENT RATINGS**  
 ALL RATINGS ARE BASED ON 3 FPS VELOCITY, 65° EAT

TUBE SIZE	CATALOG DESIGNATION	FIN SIZE HEIGHT X WIDTH	FINS PER FT.	FIN THICKNESS IN INCHES	TIERS AND CENTERS IN INCHES	MTG. HEIGHT IN INCHES	STEAM 215°F FACTOR	HOT WATER (AVG.)									
								200°	190°	180°	170°	160°	150°	140°	130°	120°	
								CORRECTION FACTORS FOR AVERAGE WATER TEMPERATURES									
								1.00	0.86	0.78	0.69	0.61	0.53	0.45	.40	.33	.26
1"	R11	3-3/4" x 2-3/4"	40	.024	1	14-1/4	910	780	710	630	560	480	410	360	300	240	
1"	R15	5" x 2-3/4"	50	.024	1	14-1/4	1100	950	860	760	670	580	500	440	360	290	
1-1/4"	R16	5" x 2-3/4"	50	.024	1	14-1/4	1150	990	900	790	700	610	520	460	380	300	