

CONVECTOR

Submittal

FS-A / FSG-A
Flat Top Cabinet
Wall/Floor Mtd.

Specification

FS-A Open Inlet

FRONT and LINER:

STYLE: Front Outlet
OUTLET: Stamped Louvers
Pencil Proof

LENGTHS: 20" thru 64" in 4" Increments
MAT'L: Cabinet Front and Liner

- ☐ 18 Ga./20 Ga. CRS (Std)
- ☐ 18 Ga./18 Ga. CRS (Opt'l)
- ☐ 16 Ga./20 Ga. CRS (Opt'l)
- ☐ 16 Ga./18 Ga. CRS (Opt'l)
- ☐ 16 Ga./16 Ga. CRS (Opt'l)
- ☐ 14 Ga./20 Ga. CRS (Opt'l)
- ☐ 14 Ga./18 Ga. CRS (Opt'l)
- ☐ 14 Ga./16 Ga. CRS (Opt'l)
- ☐ 14 Ga./14 Ga. CRS (Opt'l)

FINISH: ☐ Baked Powder Prime
☐ Baked Powder Color (Opt'l)
☐ 18 Ga./20 Ga. SS (Opt'l)
☐ 18 Ga./18 Ga. SS (Opt'l)
☐ 16 Ga./20 Ga. SS (Opt'l)
☐ 16 Ga./18 Ga. SS (Opt'l)
☐ 16 Ga./16 Ga. SS (Opt'l)

ELEMENT:

COIL: Bronze Header 3/4" NPT
w/Copper Tube/Alum Fins
(Mechanically Expanded).

HEADER CONNECTIONS:

- ☐ Single Header Both Ends (Std)
- ☐ Single Inlet 1 End / Dual Inlet
1 End (Opt'l)
- ☐ Dual Inlet Both Ends (Opt'l)

FSG-A Louvered Inlet

OPTIONAL ACCESSORIES:

DAMPER: Damper Blades Factory Installed
☐ Knob Damper (Opt'l)
☐ Tamper Resistant (Opt'l)

ACCESS DOORS:

- ☐ (Opt'l)

INSULATION:

- ☐ Back Only (Opt'l)
- ☐ Back, Sides, Top (Opt'l)

PIPING KNOCKOUT:

- ☐ (Opt'l)

4" END POCKETS:

- ☐ LH (Opt'l)
- ☐ RH (Opt'l)
- ☐ Both Ends (Opt'l)

PERFORATED FRONT: Consult Factory


- ☐ 16 Ga. (Opt'l)
- ☐ 14 Ga. (Opt'l)

FS-A Open Inlet

FSG-A Louvered Inlet

TYPE FS-A / FSG-A

MODEL	D	L	H	B	J
4xx-18	4-1/4	20,24,28,	18	2-1/8	2
4xx-20		32,36,40,	20		
4xx-24		44,48,52,	24		
4xx-26		56,60,64,	26		
4xx-32			32		
6xx-18	6-1/4	20,24,28,	18	3-1/8	4
6xx-20		32,36,40,	20		
6xx-24		44,48,52,	24		
6xx-26		56,60,64,	26		
6xx-32			32		
8xx-18	8-1/4	20,24,28,	18	4-1/8	6
8xx-20		32,36,40,	20		
8xx-24		44,48,52,	24		
8xx-26		56,60,64,	26		
8xx-32			32		



NOTE: When adding end pockets, liner and front length increase.

Vulcan
RADIATOR

260 North Elm St., Westfield, MA 01085
(413) 568-9571
www.vulcanrad.com



PROJECT: _____ DATE: _____

LOCATION: _____

ARCHITECT: _____

ENGINEER: _____

CONTRACTOR: _____

PO NUMBER: _____

STEAM RATINGS IN BTU/H (215°F at 65°F EAT)

DEPTH IN INCHES	LENGTH IN INCHES	FRONT OUTLET, NOMINAL LINER HEIGHT *TYPE FS-A				
		18"	20"	24"	26"	32"
4	20	2230	2495	2830	2930	3120
	24	2760	3145	3625	3720	3985
	28	3310	3815	4345	4465	4775
	32	3865	4490	5110	5255	5665
	36	4370	5160	5880	6025	6505
	40	4895	5810	6600	6790	7320
	44	5425	6480	7390	7560	8160
	48	5950	7105	8110	8350	8975
	52	6550	7800	8855	9070	9745
	56	7030	8450	9625	9865	10630
	60	7655	9120	10345	10610	11400
	64	8135	9790	11135	11400	12290
6	20	3240	3625	4250	4390	4850
	24	4030	4560	5375	5570	6170
	28	4850	5520	6480	6670	7370
	32	5615	6480	7610	7870	8690
	36	6430	7390	8690	9025	9935
	40	7250	8375	9815	10200	11230
	44	8065	9290	10920	11350	12480
	48	8880	10250	12025	12455	13705
	52	9745	11185	13105	13535	14905
	56	10510	12145	14230	14735	16225
	60	11400	13055	15310	15840	17425
	64	12190	14040	16440	17065	18770
8	20	4030	4535	5040	5135	5570
	24	5110	5760	6360	6575	7105
	28	6385	6960	7680	7895	8520
	32	7560	8185	9025	9310	10055
	36	8710	9385	10390	10705	11545
	40	9865	10630	11760	12070	13055
	44	11040	11830	13055	13440	14545
	48	11950	12935	14400	14810	16080
	52	13465	14230	15670	16105	17425
	56	14615	15505	17090	17570	19010
	60	15770	16655	18335	18840	20375
	64	16775	17880	19750	20330	21960

DEPTH IN INCHES	LENGTH IN INCHES	FRONT OUTLET, NOMINAL LINER HEIGHT *TYPE FSG-A				
		18"	20"	24"	26"	32"
4	20	2163	2420	2773	2871	3089
	24	2677	3051	3553	3646	3945
	28	3211	3701	4258	4376	4727
	32	3749	4355	5008	5150	5608
	36	4239	5005	5762	5905	6440
	40	4748	5636	6468	6654	7247
	44	5262	6286	7242	7409	8078
	48	5772	6892	7948	8183	8885
	52	6354	7566	8678	8889	9648
	56	6819	8197	9433	9668	10524
	60	7425	8846	10138	10398	11286
	64	7891	9496	10912	11172	12167
6	20	3046	3408	4038	4171	4753
	24	3788	4286	5106	5292	6047
	28	4559	5189	6156	6337	7223
	32	5278	6091	7230	7477	8516
	36	6044	6947	8256	8574	9736
	40	6815	7873	9324	9690	11005
	44	7581	8733	10374	10783	12230
	48	8347	9635	11424	11832	13431
	52	9160	10514	12450	12858	14607
	56	9879	11416	13519	13998	15901
	60	10716	12272	14545	15048	17077
	64	11459	13198	15618	16212	18395
8	20	3667	4127	4687	4776	5403
	24	4650	5242	5915	6115	6892
	28	5810	6334	7142	7342	8264
	32	6880	7448	8393	8658	9753
	36	7926	8540	9663	9956	11199
	40	8977	9673	10937	11225	12663
	44	10046	10765	12141	12499	14109
	48	10875	11771	13392	13773	15598
	52	12253	12949	14573	14978	16902
	56	13300	14110	15894	16340	18440
	60	14351	15156	17052	17521	19764
	64	15265	16271	18368	18907	21301

Correction factors for BTU performance at different Average Water Temperatures, use correction factors from Table 3 of the Correction Factors page.

For other applicable correction factors see the Correction Factors page.

For assistance with ratings and selection, please use our online Specifier.

CONVECTOR BTU CORRECTION FACTORS

Table 3

CONVECTOR CORRECTION FACTORS Based on Section 35.4 ASHRAE HVAC Systems and Equipment					
AVERAGE WATER TEMPERATURE (°F)	ENTERING AIR TEMPERATURE (°F)				
	(STD)				
	55°	60°	65°	70°	75°
100°	0.17	0.14	0.12	0.09	0.07
110°	0.23	0.20	0.17	0.14	0.12
120°	0.29	0.26	0.23	0.20	0.17
130°	0.35	0.32	0.29	0.26	0.23
140°	0.43	0.39	0.35	0.32	0.29
150°	0.50	0.46	0.43	0.39	0.35
160°	0.58	0.54	0.51	0.47	0.43
170°	0.67	0.63	0.58	0.54	0.51
180°	0.76	0.71	0.67	0.63	0.58
190°	0.85	0.81	0.76	0.71	0.67
200°	0.95	0.90	0.85	0.81	0.76
210°	1.05	1.00	0.95	0.90	0.85
215° (STD)	1.10	1.05	1.00	0.95	0.90
220°	1.15	1.10	1.05	1.00	0.95
230°	1.26	1.20	1.15	1.10	1.05
240°	1.37	1.32	1.26	1.21	1.15
250°	1.47	1.43	1.37	1.32	1.27

Table 4

CORRECTION FACTORS FOR STEAM PRESSURES OTHER THAN 1 PSI GAUGE*						
FACTOR	PRESSURE PSI GAUGE					
	5	10	15	20	25	50
	1.12	1.25	1.36	1.46	1.56	1.93
*Apply factors shown above to the ratings shown on the 215°F ratings page.						

Note: Max Recommended operating pressure 150 PSIG, (365.9°F).
For conversion from steam to hot water, use correction factors shown in Table 3.

Table 5

CORRECTION FACTORS FOR ACCESS DOORS								
Length	Free Standing, Non-Recessed Non-Standard Access Door Locations				Semi-Recessed or Fully Recessed Non-Standard Access Door Locations			
	3 or 4	3 & 4	5 or 6	5 & 6	3 or 4	3 & 4	5 or 6	5 & 6
20"	0.940	0.880	0.820	0.650	0.975	0.950	0.925	0.850
24"	0.950	0.910	0.860	0.720	0.980	0.960	0.940	0.880
28"	0.960	0.920	0.890	0.770	0.982	0.968	0.948	0.902
32"	0.970	0.940	0.890	0.800	0.985	0.972	0.955	0.918
36"	0.970	0.940	0.920	0.830	0.988	0.975	0.962	0.925
40"	0.970	0.950	0.920	0.850	0.990	0.978	0.970	0.932
44"	0.980	0.950	0.930	0.860	0.990	0.980	0.970	0.940
48"	0.980	0.960	0.940	0.880	0.990	0.982	0.970	0.948
52"	0.980	0.960	0.950	0.890	0.992	0.985	0.978	0.955
56"	0.980	0.960	0.950	0.890	0.992	0.985	0.978	0.955
60"	0.980	0.970	0.950	0.900	0.992	0.985	0.978	0.955
64"	0.980	0.970	0.950	0.910	0.992	0.988	0.978	0.962

Note: Derating factors do not apply to units with end pockets.

Table 6

WATER FLOW IN G.P.M.	PRESSURE LOSS IN FEET OF WATER		
	4 INCH MODELS	6 INCH MODELS	8 INCH MODELS
.25	0.044	—	—
.50	0.160	0.070	0.046
1	0.597	0.270	0.167
2	2.220	1.047	0.616
3	—	2.260	1.367
4	—	3.793	2.380
5	—	—	3.673


Charted figures showing pressure drop through Convectors with forced hot water. Used for determining pressure head requirement. Based on 64" length units, but applicable to shorter units, as most loss is due to headers.

ADDITIONAL CORRECTION FACTORS ON NEXT PAGE

CONVECTOR BTU CORRECTION FACTORS

GALLONS PER MINUTE OF HOT WATER REQUIRED

Table 7




OUTPUT-FLOW RATE CORRECTIONS

Table 8

Convactor Depth	Tubes per Element	Min. Flow Rate (0.25 Ft./Sec.) GPM	MBH Based on T.D. & Min. Flow Rate			
			10TD	20TD	30TD	40TD
4"	2	.15	0.750	1,500	2,250	3,000
6"	3	.225	1.125	2,250	3,375	4,500
8"	4	.30	1.500	3,000	4,500	6,000

NOTE: Table 8 shows MBH which result at specific water temperature drops and minimum water flow rates which are required to maintain turbulent flow within element tubes.

CONVECTOR COIL



NOTE: When ordering convectors with end pockets always refer to the standard unit length. The overall physical length will increase by 4" for each end pocket. The coil length will remain the standard size. Coil fins are 2-1/2" high by width shown above and are mechanically bonded to copper tube at 6 fins per inch.

